

## Retro-reflective sheeting which has a 3 year performance life.

High tensile strength top layer makes it ideal for temporary signs, labels and decals.

### **YSL M-Lite®**

**YSL M-Lite®** is high performance, durable retro-reflective material intended for use on advertising signs, temporary work zones and other non specified signage.

It's unique microglass bead construction using **mbead®** clearview component provides an extremely high level of reflectivity.

The **YSL M-Lite®** retro-reflective sheeting delivers high contrast reflectivity values. This provides longer distance visibility for drivers to view, recognise and manoeuvre accordingly.





### The Yeshili Group

### Zhejiang Fangyuan Yeshili Reflective Material Co Ltd.

No 292 Donghai Street, Economic Development Zone, Taizhou City 318000, Zhejiang, China T: 86 576 88209742

F: 86 576 88205396 E: ysl@chinaysl.com Taizhou Fangyuan Reflective Material Co., Ltd. West 3 Road, Chengguan, Xianju, Zhejiang, China T: 86 576 87726971

F: 86 576 87726972 E: yuki@yslreflectives.com

### **YSL M-Lite® Series 300 Features**

Properties: A glass bead retro-reflective material with a 3 year performance life. Available in 6 colours.

Application: Ideal for Commercial Signage - advertising, promotional, car park signs, construction site signs and temporary labels.

Features: High tensile strength top layer, excellent retro-reflectivity, available in PET and Acrylic.

### YSL M-Lite® 300 PET

None tearable, can be screen printed with PET Type inks.

### YSL M-Lite® 300 Acrylic

Tearable, can be screen printed, Ink-Jet printed and is excellent for computer cutting and has good extensibilty.

### **The Viz Group**

### Viz Reflectives

Unit 4, Tricketts Lane, Nantwich, Cheshire CW5 6PZ T: + 44 (0)1270 650826

T: + 44 (0)1270 650826 F: + 44 (0) 560 3438746 E: info@viz-group.com

# Viz Europe s.r.l. via A. Berlese, 1 24124 Bergamo, Italy T. +39 035 36 25 10 F. +39 035 36 25 04 E: vizeuropa@vizeuropa.com

## **Promotional Grade**

## Series 300 Product & Application Data

		White	Yellow	Red	Green	Blue	Orange
	300 PET Series	3101	3102	3103	3104	3105	3106
Product Codes	300 Acrylic Series	3201	3202	3203	3204	3205	3206
	300 PET/Acrylic Series	3101A	3102A	3103A	3104A	3105A	3106A

### Typical measurement of retro-reflection cd/lux/m<sup>2</sup>

Series	Type of Adhesive	Observation Angle	Entrance Angle	○ White	Yellow	Red	Green	Blue	Orange
300	Pressure Sensitive	0.2°	-4°	50	25	8	5	3.5	-

Roll Specifications	Width	Length	Roll Weight	Box Dimensions
Imperial	48"	50 yards	50.7 lb	53.1" x 7.9" x 7.1"
Metric	1.22 metres	45.7 metres	23 kg	135 cm x 20 cm x 18 cm
Other sizes available:	30" 0.762 metres	50 yards 45.7 metres		
	36" 0.91 metres	50 yards 45.7 metres		
	30" 0.762 metres	100 yards 91.4 metres		

### Adhesive sheet base material

YSL M-Lite® reflective sheeting is suitable for use on steel, aluminium and rigid PVC base boards. For best results treated aluminium base boards are recommended. When using a plastic base board it is suggested that the adhesion is tested on a small area before application.

### Adhesion temperature

The temperature of both the base board and the YSL M-Lite® sheeting should be synchronized to 18°C or above, with the optimum temperature being 20° - 25°C.

### **Application method**

In a clean environment, cut the reflective sheeting according to the board size. For large surface areas, machine application is recommended. Smaller areas can be hand-applied. After fixing in position use a squeegee to remove bubbles and wrinkles from the sheeting.

### Storage

YSL M-Lite® reflective sheeting should be stored in a clean, well ventilated environment. The optimum temperature for storage is 15° - 30°C with a humidity of 30-60 %. Unused rolls should be tightened and re-wrapped. All rolls should be stored horizontally to avoid compression and stored out of direct sunlight.

### Usage of the product

YSL M-Lite® reflective sheeting has a wide variety of applications. These include road, aviation and railway signage, advertising decoration and so on. Each grade of YSL M-Lite® reflective sheeting offers long term reflective performance and weather resistance. For the individual performance criteria please refer to the material data sheets.

For further information on product usage see the **YSL M-Lite**® application manual.

### **Products available**

PRODUCT DETAILS					APPLICATION				SUBSTRATE			PRINTABLE			
Series	Product Code	Substrate	Colour - Other colours available	Product Lifespan years	BS EN 12899-1 2008	Temporary Signage	Temporary Barriers	Advertising Signage	Fixed Permanent Signage	Road Cones and Delineators	Tearable	Non-Tearable	CAD CUT	Ink Jet	Screen Printable
300 Promotional Grade	3100 3100A 3200	PET PET/Acrylic Acrylic	0	3	- - -	\(  \)	1 1	1 1	-		- - -	√ √ -	- - •	- 1 1	<b>&gt; &gt; &gt;</b>
500 Engineering Grade	5100 5200	PET Acrylic	0	5	-	1	√ √	1	1	-	-	<b>/</b> -	- 🗸	- ./	✓ ✓
700 Engineering Grade	7200	Acrylic	<b></b>	7	/	/	1	1	1	-	>	-	1	/	1
1000 High Intensity Grade	1100 1200 1800	PET Acrylic PVC	0.000	7 10 3	- / -	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	\frac{1}{\sqrt{1}}	\(  \)	✓ ✓ -	- - -	- √	✓ - -	-	- 1	/ /